UAB "BY & N"
Jurbarko g. 2-206, LT-47183 Kaunas
Oršos g. 7-402, LT-09300 Vilnius
www.ledlife.lt
2026-11-22

LED Panel IP44

130 [lm/W] | CRI≥80 | Dimming | 0,9 PF | IP44 | RoHS | CE

Widely used in Factory, Workshop, Warehouse, Logistics Center Exhibition Hall, Gymnasium, Shipyards, Mining, Gas Station, Supermarket, Other Places






Light characteristics

Lighting Effectiveness	100 lm/W; 130 lm/W
Beam Angle	110°
Temperature (CCT)	3000K- 6000K
Color Rendering Index (CRI)	RA≥80
Unified Glare Rating (UGR)	<21; <19
LED chip type	2835; 4014

Common parameters

IP Rating	IP44
Housing	Aluminum 6063; Stainless steel
Warranty	3 years; 5 years
Certificates	CE; ROHS

Electrical data

Voltage	200-240V AC
Power Factor (PF)	>0.90
Power supply brand	LIFUD

Operating conditions

Life time (LM80)	≥50000 h
Ambient Temperature	nuo -20°C iki +45°C
Dimmable	0-10V; DALI; TRIAC

Model parameters

Model	Power	Light flux	Size (mm)
LP2332NW43X	32W	4160 lm	1195x295
LP2136NW4-R	36W	3600 lm	1195x145
LP6640NW-R	40W	4000 lm	595x595
LP6640NW+R	40W	4000 lm	595x595
LP2340NW4-R	40W	4000 lm	1195x295
LP2665NW4-R	65W	6300 lm	1195x595