UAB "BY & N"
Jurbarko g. 2-206, LT-47183 Kaunas
Oršos g. 7-402, LT-09300 Vilnius
www.ledlife.lt
2026-11-23

Underwater Luminaire "Pool-2"

Widely used in Factory, Workshop, Warehouse, Logistics Center Exhibition Hall, Gymnasium, Shipyards, Mining, Gas Station, Supermarket, Other Places






Light characteristics

Lighting Effectiveness	≥100 lm/W
Beam Angle	30°; 45°; 60°
Temperature (CCT)	2700-6500K; R; G; B; RGB
Color Rendering Index (CRI)	RA≥80
LED chip brand	EPISTAR; OSRAM

Common parameters

IP Rating	IP68
Housing	304 Stainless housing+Tempered glass
Warranty	2 yrs
Certificates	CE

Electrical data

Power Factor (PF)	>0.90

Operating conditions

Life time (LM80)	≥50,000 h
Ambient Temperature	-20°C to +50°C

Model parameters

Model	Power	Light flux	LED Chips (pcs)	Hole size (mm)	Size (mm)	Weight (kg)
UWR-03X1NXRL	3x1W	300 lm	3	Φ90	ф100x75	0,55
UWR-06X1NXRL	6x1W	600 lm	6	Φ115	ф125x110	0,80
UWR-09X1NXRL	9x1W	900 lm	9	Φ140	ф150x100	1,1
UWR-12X1NXRL	12x1W	1200 lm	12	Φ140	ф150x100	1,1
UWR-15X1NXRL	15x1W	1500 lm	15	Φ170	ф180x110	1,8
UWR-18X1NXRL	18x1W	1800 lm	18	Φ170	ф180x110	1,8
UWR-24X1NXRL	24x1W	2400 lm	24	Φ200	ф210x130	2
UWR-55X0NRRG	55W	5500 lm	60	Φ330	ф350x180	5,3
UWR-60X0NRRG	60W	6000 lm	60	Φ330	ф350x180	5,3