

UAB "BY & N"
Jurbarko g. 2-206, LT-47183 Kaunas
Oršos g. 7-402, LT-09300 Vilnius
www.ledlife.lt
2026-11-22

Facade lamp F37

>Outdoor floodlight of modern design, designed to illuminate certain outdoor spaces and building facades. It can be equipped with various angles of light propagation.


Light characteristics

Lighting Effectiveness	≥90 lm/W
Beam Angle	3,5°; 6,5°; 10°; 10°x40°; 15°; 24°; 25°; 36°; 40°; 60°
Temperature (CCT)	3000K; 4000K; 6000K; RGB
Color Rendering Index (CRI)	RA≥80
LED chip type	3535

Common parameters

IP Rating	IP66
IK rating	IK08
Housing	Aluminum
Warranty	5 yrs
Certificates	CE; ROHS

Electrical data

Voltage	176-265V AC
Power Factor (PF)	>0,9

Operating conditions

Life time (LM80)	≥50000 h
Ambient Temperature	-20°C to +40°C

Model parameters

Model	Power	Light flux	Size (mm)	Weight (kg)
FLF-003N6-G	3W	270 lm	53x60x85	0,2
FLF-006N6-G	6W	540 lm	53x60x85	0,2
FLF-009N6-G	9W	810 lm	100x100x100	1,2
FLF-016N6-G	16W	1440 lm	100x100x100	1,2
FLF-018N6-G	18W	1620 lm	150x105x150	2,6
FLF-032N6-G	32W	2880 lm	150x105x150	2,6