UAB "BY & N"
Jurbarko g. 2-206, LT-47183 Kaunas
Oršos g. 7-402, LT-09300 Vilnius
www.ledlife.lt
2026-11-22

SURFACE LIGHT ECO

The lamp is suitable for use in common corridors, staircases, passage areas. A wide selection of power and functional features. Can be equipped with a motion sensor and an emergency module.






Light characteristics

Lighting Effectiveness	≥90 lm/W
Beam Angle	120°
Temperature (CCT)	3000K-4000K
Color Rendering Index (CRI)	RA≥80
LED chip type	SMD2835

Common parameters

IP Rating	IP20
Housing	Metal; PMMA
Housing colour	White
Warranty	3 yrs
Certificates	CE; ROHS

Electrical data

Voltage	220-240V AC

Operating conditions

Life time (LM80)	≥35000 h

Model parameters

Model	Power	Light flux	Size (mm)
CL-08NAW-R	8W	720 lm	ф210x60
CL-12NAW-R	12W	1080 lm	ф260x65
CL-18NAW-R	18W	1620 lm	ф330x65
CL-24NAW-R	24W	2160 lm	ф380x65
CL-32NAW-R	32W	2880 lm	ф480x65
CL-43NAW-R	43W	3870 lm	ф580x70