

PASTATOMAS PARKO ŠVIESTUVAS RGBY

Nedidelės galios (15W ir 2x15W) dekoratyvinis šviestuvas skirtas apšviesti žaliąsias erdves parkuose, viešose poilsio aikštelėse, namų valdos sklypuose. Galimos šviesos spalvos: 3000K, 4000K, 6000K, Raudona, Žalia, Melyna, ir Geltona. Šviestuovo aukštis 100 cm.



Bendrieji parametrai

Šviestuovo efektyvumas	≥100 lm/W	Apsaugos klasė	IP65
Šviesos spalva (CCT)	3000K; 4000K; 6000K; R; G; B; Y	Spalvų atgavos indeksas (CRI)	RA≥80
LED šviestukų gamintojas	EPISTAR	Šviestuovo ilgaamžiškumas	≥35000 h
Veikimo aplinkos temperatūra	nuo -35°C iki +45°C	Naudojama įtampa	220-240V AC
Šviestuovo elektros saugos klasė	I	Korpusas	Aliuminis
Garantija	3 metai	Sertifikatai	CE; RoHS

Modelis	Galia	Šviesos srautas	Dydis (mm)
PSL-15N-G	15W	1500 lm	1000x80x200
PSL-30N-G	15W x2	3000 lm	1000x80x200



W- 3017

Product Dimensions(mm)




Product description:
Lamp housing is made by die cast aluminum, surface treatment for electrostatic powder coating.
Diffuser is made by high quality UV-stable PC lens.
High pure aluminium reflector.
Sealed lamp housing.

TECHNOLOGY DATA

Protection grade	Corrosion proof capability	Working condition	Material class	Power voltage	Max power
IP65	II	-35°C ~ +45°C	class I	220V~1.2P/0.5/0.4u	15 W

W- 3018

Product Dimensions(mm)



Product description:
Lamp housing is made by die cast aluminum, surface treatment for electrostatic powder coating.
UV-stable PC lamp cover.
Sealed lamp housing.

TECHNOLOGY DATA

Protection grade	Corrosion proof capability	Working condition	Material class	Power voltage	Max power
IP65	II	-35°C ~ +45°C	class I	220V~1.2P/0.5/0.4u	15 W x 2