

PASTATOMAS PARKO ŠVIESTUVAS / TAKUI 2

Nedidelės galios dekoratyvinis šviestuvas skirtas apšviesti žaliąsias erdves parkuose, viešose poilsio aikštelėse, namų valdos sklypuose. Galimos šviesos spalvos: 3000K, 4000K, 6000K. Korpusas dažytas miltelininiu būdu.



Bendrieji parametrai

Šviestuvo efektyvumas	≥100 lm/W	Apsaugos klasė	IP65
Šviesos spalva (CCT)	3000K; 4000K; 6000K	Spalvų atgavos indeksas (CRI)	RA≥80
LED šviestukų gamintojas	EPISTAR	Šviestuvo ilgaamžiškumas	≥35000 h
Veikimo aplinkos temperatūra	nuo -35°C iki +45°C	Naudojama įtampa	200-240V AC
Šviestuvo elektrosaugos klasė	I	Korpusas	Aliuminis
Garantija	3 metai	Sertifikatai	CE; RoHS

Modelis	Galia	Šviesos srautas	Dydis (mm)
PSL-05N02-G	5W	500 lm	210x102
PSL-05N04-G	5W	500 lm	410x102
PSL-10N06-G	10W	1000 lm	610x102
PSL-10N08-G	10W	1000 lm	810x102

W- 3023

Product Dimensional Chart



Product description:
Lamp housing is made by die cast aluminum, surface treatment for electrostatic powder coating.
Diffuser is made by high quality UV-stable PC lens.
High open aluminum reflector.
Sealed lamp housing.

TECHNOLOGY DATA

Power grade	Dimension possibility	Working condition	Installation	Power voltage	Life span
5W	II	-35°C ~ +45°C	10m	220V/110V/50Hz	50,000h

